

APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR(S): Takehiro IKEDA
Ichiro OKAJIMA
Narumi UMEDA

INVENTION: MOBILE COMMUNICATION SYSTEM AND
DISTRIBUTED BROADCAST
INFORMATION CONTROL METHOD IN
MOBILE COMMUNICATION SYSTEM

S P E C I F I C A T I O N

10054734-44301
COPY 4E245001

~~SECRET~~ This application is based on Patent Application No. 2000-345785 filed November 13, 2000 in Japan, the content of which is incorporated hereinto by reference.

5

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

10 The present invention relates to a mobile .
communication system and a distributed broadcast
information control method in the mobile communication
system, which are characterized by the broadcast
information control in the mobile communication system
15 that offers communication services from a base station
to a mobile station via a radio channel.

DESCRIPTION OF THE RELATED ART

20 In a mobile communication system, a base station
periodically transmits various types of broadcast
information such as regulation information and
available channel information of each area to mobile
stations via a broadcasting channel. Receiving such
25 broadcast information, the mobile station can learn the
current conditions of the mobile communication system.
Fig. 1 shows the contents of a broadcast information

message defined in a PDC (Personal Digital Cellular) system, as an example of the broadcast information.

In the broadcasting control in the conventional mobile communication system, an RNC (Radio Network
5 Controller), a higher level control office of the base station that controls multiple base stations, prepares the broadcast information and transmits it to the base stations in a point-to-point manner. Accordingly, the conventional system has a problem in that the load
10 concentrated on the RNC increases with the number of the base stations controlled by the RNC.

SUMMARY OF THE INVENTION

15 It is therefore an object of the present invention to implement broadcasting control capable of obviating the need of the RNC by preparing the broadcast information autonomously in a distributed manner by interconnecting the base stations two-dimensionally to
20 enable them to exchange information directly.

According to a first aspect of the present invention, there is provided a mobile communication system including multiple base stations that are interconnected two-dimensionally and offer radio
25 communication services in individual service areas, each of the base stations comprising: information exchanging means for exchanging information about

10054734-11301
broadcast information with other base stations; and
broadcast information generating means for generating
broadcast information about a broadcasting area of the
base station from information about broadcast
5 information that is sent from the other base stations
and obtained by the information exchanging means.

Here, the multiple base stations may be
interconnected via an IP network.

The information exchanging means of each of the
10 base stations may send its own information about the
broadcast information to other base stations using a
multicast address.

The information about the broadcast information
may include information for controlling coverage of the
15 information about the broadcast information.

The information for controlling the coverage of
the information may include a hopping number field
value.

The information for controlling the coverage of
20 the information may include latitude and longitude
information of a source base station and its desired
reception coverage value.

The mobile communication system may further
comprise a mobile station that comprises means for
25 acquiring broadcast information about an area other
than a broadcasting area the mobile station is visiting,
from a base station in the broadcasting area the mobile

station is visiting.

According to a second aspect of the present invention, there is provided a distributed broadcast information control method in a mobile communication system including multiple base stations that are interconnected two-dimensionally and offer radio communication services in individual service areas, each of the base stations comprising the steps of: exchanging information about broadcast information with other base stations; and generating broadcast information about a broadcasting area of the base station from information about broadcast information that is sent from the other base stations.

Here, the multiple base stations may be interconnected via an IP network.

Each of the base stations may send its own information about the broadcast information to other base stations using a multicast address when exchanging the information.

The information about the broadcast information may include information for controlling coverage of the information about the broadcast information.

The information for controlling the coverage of the information may include a hopping number field value.

The information for controlling the coverage of the information may include latitude and longitude

information of a source base station and its desired reception coverage value.

The distributed broadcast information control method in the mobile communication system may further
5 comprise the step of causing a mobile station to acquire broadcast information about an area other than a broadcasting area the mobile station is visiting, from a base station in the broadcasting area the mobile station is visiting.

10 According to a third aspect of the present invention, there is provided a base station that offers radio communication services in a service area, the base station comprising: information exchanging means for exchanging information about broadcast information
15 with other base stations; and broadcast information generating means for generating broadcast information about a broadcasting area of the base station from information about broadcast information that is sent from the other base stations and obtained by the
20 information exchanging means.

Here, the information exchanging means may send its own information about the broadcast information to other base stations using a multicast address.

The above and other objects, effects, features and
25 advantages of the present invention will become more apparent from the following description of embodiments thereof taken in conjunction with the accompanying

drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a table showing the relationship of Figs. 1A and 1B;

 Fig. 1A is a block table showing an example of the contents of a broadcast information message;

10 Fig. 1B is a block table showing an example of the contents of a broadcast information message;

 Fig. 2 is a diagram illustrating an embodiment 1 of the mobile communication system in accordance with the present invention;

15 Fig. 3 is a diagram illustrating an embodiment 2 of the mobile communication system in accordance with the present invention;

 Fig. 4A is a diagram illustrating a multicast packet format in the embodiment 2;

20 Fig. 4B is a flowchart illustrating the operation when each base station in the embodiment 2 receives a multicast packet;

 Fig. 5 is a diagram illustrating an embodiment 3 of the mobile communication system in accordance with the present invention;

25 Fig. 6A is a diagram illustrating a multicast packet format in the embodiment 3;

 Fig. 6B is a flowchart illustrating the operation

when each base station in the embodiment 3 receives a multicast packet;

Fig. 7 is a diagram illustrating an embodiment 4 of the mobile communication system in accordance with the present invention;

Fig. 8A is a diagram showing a structure of a broadcast information acquisition request packet format;

Fig. 8B is a diagram showing another structure of a broadcast information acquisition request packet format;

Fig. 8C is a diagram showing a structure of a broadcast information acquisition response packet format; and

Fig. 9 is a block diagram showing a configuration of a base station used in the embodiments 1-4 of the mobile communication system in accordance with the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The invention will now be described with reference to the accompanying drawings.

In the following embodiments, a base station is assumed to have a configuration as shown in Fig. 9 as a component constituting the embodiments in accordance with the present invention. Specifically, the base

station comprises a transmitting section 1 for transmitting necessary information to a mobile station; a receiving section 2 for receiving a signal transmitted from the mobile station; an information
5 exchanging section 3 for exchanging information about broadcast information with other base stations via an IP (Internet Protocol) network 6; a broadcast information generating section 4 for preparing broadcast information about the broadcasting area the
10 base station belongs to from the information about the broadcast information the information exchanging section 3 collects from the other base stations; and a control section 5 for controlling the transmitting section 1, the receiving section 2, the information
15 exchanging section 3 and the broadcast information generating section 4. The information exchanging section 3, broadcast information generating section 4 and control section 5 can be constructed by a computer system. The computer system implements the functions
20 of the information exchanging section 3, broadcast information generating section 4 and control section 5 by comprising a CPU, a ROM (and a hard disk drive) for storing programs to execute the present invention, a RAM for providing the CPU with a work area, and an
25 interface for accessing the IP network 6, and by executing the programs stored in the ROM (and a hard disk drive) by the CPU. The operations of the following

embodiments are executed under the control of the control section 5. On the other hand, the mobile station comprises in its internal memory a program storing area for storing programs to execute data processing that will be described below, and a temporarily storing area of data, and has its internal CPU execute the programs.

(EMBODIMENT 1)

Fig. 2 is a block diagram showing an embodiment 1 that implements the broadcast information control in accordance with the present invention in the IP network.

In the present embodiment 1, each base station (#1-#N) has an IP address and a base station multicast address as follows.

Node	IP address	Multicast address
base station #1	xxx.xxx.0.0	xxx.xxx.1.0
base station #2	xxx.xxx.0.1	xxx.xxx.1.0
:	:	:
base station #N	xxx.xxx.0.N	xxx.xxx.1.0

Each base station sends its own system information to all the base stations using the multicast address. Each base station generates its broadcast information from the system information of the other base stations

and its own system information.

(EMBODIMENT 2)

Fig. 3 is a block diagram showing an embodiment 2 that implements the broadcast information control in accordance with the present invention in the IP network.

In the present embodiment 2, each base station has an IP address and a base station multicast address as in the foregoing embodiment 1.

Each base station sends its own system information using the multicast address. In this case, the transmission packet includes a hopping number field, in which a hopping number field value is set at the transmission to control the coverage of the packet.

Fig. 4A shows a format of the multicast packet, and Fig. 4B shows the operating flow at the time when the base station receives the multicast packet. The operation is carried out by the data processing unit in each base station. More specifically, receiving the packet, each base station detects the hopping number field value of the received multicast packet at step S1. When the value is greater than one, it captures the information at step S2, reduces the hopping number field value by one, and transfers it to other base stations. On the other hand, when the hopping number field value of the received packet is one at step S1, although the base station captures the

information at step S3, it does not transfer it to other base stations.

To produce the broadcast information, since it is enough for only the base stations close to each other to exchange information, such control is very effective in terms of reducing the traffic of the network.

Each base station generates the broadcast information from its own system information and the system information of other base stations received.

10 (EMBODIMENT 3)

Fig. 5 is a block diagram showing an embodiment 3 that implements the broadcast information control in accordance with the present invention in the IP network.

15 In the present embodiment 3, each base station has an IP address and a base station multicast address as in the foregoing embodiment 1.

Each base station sends its own system information using the multicast address. In this case, the transmission packet includes latitude and longitude information about a source base station, so that the coverage of the packet is controlled by a desired packet reception coverage value (D_{desire}) that is set at the transmission.

25 Fig. 6A shows a format of the multicast packet, and Fig. 6B shows the operating flow at the time when the base station receives the multicast packet. The

operation is carried out by the data processing unit in each base station. More specifically, receiving the packet, each base station calculates the distance D between the base station and the source base station from its own latitude and longitude and from the latitude and longitude information about the source base station in the received multicast packet at step S11. At the next step S12, the data processing unit compares the distance D with the desired packet reception coverage value D_{desire}. If $D \leq D_{desire}$, it captures the information in the packet at step S13, and transfers it to other base stations at step S14. In contrast, if $D > D_{desire}$ at step S12, it discards the packet at step S15 without transferring it.

To produce the broadcast information, since it is enough for only the base stations close to each other to some extent to exchange information, such control is very effective for reducing the traffic of the network.

Each base station generates the broadcast information from its own system information and the system information of other base stations received.

(EMBODIMENT 4)

Fig. 7 is a block diagram showing an embodiment 4 of the broadcast information control in accordance with the present invention.

In the present embodiment 4, a mobile station MS

carries out control using the broadcast information of neighboring base stations when it wishes to move to a particular destination with continuing its communication. Here, a description is made assuming
5 that the broadcasting area consists of a single cell.

First, the mobile station MS transmits a broadcast information acquisition request packet using the base station multicast address. In this case, the packet coverage control based on the hopping number or the
10 latitude and longitude information as described in the embodiment 2 or 3 is applicable to the broadcast information acquisition request packet. Figs. 8(a) and 8(b) each illustrate a format of the broadcast information acquisition request packet when the
15 control is applied.

Receiving the broadcast information acquisition request packet, the base station transmits its own broadcast information to the mobile station MS using the format of the broadcast information acquisition
20 response packet. Here, the broadcast information acquisition response packet includes the latitude and longitude information of the base station that transmits the packet. Thus, the mobile station MS can move to the destination cell with always selecting
25 cells having available channels in accordance with the received broadcast information about individual stations.

According to the present invention, the base stations are two-dimensionally connected to each other, so that the base stations can directly exchange information, and generate broadcast information
5 autonomously in a distributed manner. Thus, the broadcasting control without requiring the RNC can be implemented.

The present invention has been described in detail with respect to preferred embodiments, and it will now
10 be apparent from the foregoing to those skilled in the art that changes and modifications may be made without departing from the invention in its broader aspects, and it is the intention, therefore, in the appended claims to cover all such changes and modifications as
15 fall within the true spirit of the invention.